

# Certificate of Compliance

## Certificate Number(s):

UL-US-2583644-0

## Report Reference:

E547836-20250910

## Issue Date:

2025-09-12

Issued to:

**Guangdong Bangyu Lighting Co., Ltd.**  
**Area A 8th Floor BLDG 3 No. 32 Industrial Avenue, Baofeng**  
**Community Xiaolan Town, Zhongshan, Guangdong, 528415, CN**

This certificate confirms that representative samples of:

**IFDR - Low-voltage Lighting Systems, Power Units, Luminaires and Fittings**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**UL 2108, Edition 2, Issue Date 2015-12-07, Revision Date 2024-09-27**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2583644-0  
Report reference: E547836-20250910  
Issue Date: 2025-09-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## Low-voltage Luminaire

**Model(s):** DDI-240-15-24V-XXXXK-N2, DDI-240-10-12V-XXXXK-N2, DDI-168-5-12V-XXXXK-N2, DDI-240-15-24V-XXXXK-N2-2P, DDI-120-8-24V-XXXXK-A1-N2-DGJIP67, DDI-120-5-12V-XXXXK-N2, DDI-60-8-12V-XXXXK-N2, DDI-240-15-12V-XXXXK-N2-2P, DDI-120-8-12V-XXXXK-A1-N2-DGJIP67, DDI-180-8-12V-XXXXK-N2, DDI-168-8-12V-XXXXK-N2, DDI-120-5-24V-XXXXK-N2, DDI-168-8-24V-XXXXK-N2, DDI-240-10-24V-XXXXK-N2, DDI-240-8-12V-XXXXK-N2, DDI-120-8-24V-XXXXK-N2, DDI-240-10-12V-XXXXK-N2-2P, DDI-120-8-12V-XXXXK-N2, DDI-180-8-24V-XXXXK-N2, DDI-168-5-24V-XXXXK-N2, DDI-240-8-24V-XXXXK-N2, DDI-60-8-24V-XXXXK-N2, DDI-240-15-12V-XXXXK-N2, DDI-240-10-24V-XXXXK-N2-2P *Where "XXXX" can be 2700 thru 6500 to represent the color temperature of LED.*

**Model(s):** DDI-120-8-24V-(XXK+YYK)-N2, DDI-120-8-24V-XXK+YYK-N2-UL-DGJIP67, DDI-120-8-24V-(XXK+YYK)-N2-DGJIP67, DDI-180-8-24V-XXK+YYK-N2, DDI-168-8-24V-(XXK+YYK)-N2, DDI-168-8-12V-(XXK+YYK)-N2, DDI-180-8-12V-XXK+YYK-N2, DDI-120-8-12V-(XXK+YYK)-N2-DGJIP67, DDI-168-5-12V-(XXK+YYK)3X-N2, DDI-120-5-12V-(XXK+YYK)2X-N2, DDI-120-8-24V-XXK+YYK-N2, DDI-168-8-24V-XXK+YYK-N2, DDI-120-5-24V-(XXK+YYK)2X-N2, DDI-120-8-12V-(XXK+YYK)-N2, DDI-192-8-24V-XXK+YYK-N2, DDI-120-5-24V-(XXK+YYK)3X-N2, DDI-192-8-12V-XXK+YYK-N2, DDI-168-8-12V-XXK+YYK-N2, DDI-120-8-12V-(XXK+YYK)2X-N2, DDI-120-5-12V-(XXK+YYK)3X-N2, DDI-168-5-24V-(XXK+YYK)3X-N2, DDI-120-8-12V-XXK+YYK-N2-UL-DGJIP67, DDI-120-8-12V-XXK+YYK-N2, DDI-120-8-24V-(XXK+YYK)2X-N2 *Where "XX" and "YY" can be 2.7 thru 6.5 to represent the color temperature of LED.*



David Piecuch  
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# Certificate of Compliance

## Certificate Number(s):

UL-CA-2561164-0

## Report Reference:

E547836-20250910

## Issue Date:

2025-09-12

Issued to:

**Guangdong Bangyu Lighting Co., Ltd.**  
**Area A 8th Floor BLDG 3 No. 32 Industrial Avenue, Baofeng**  
**Community Xiaolan Town, Zhongshan, Guangdong, 528415, CN**

This certificate confirms that representative samples of:  
**IFDR7 - Low-voltage Lighting Systems, Power Units,**  
**Luminaires and Fittings Certified for Canada**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**CSA C22.2 NO. 250.2, 1st Ed., Issue Date: 2020-01-01**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-2561164-0  
Report reference: E547836-20250910  
Issue Date: 2025-09-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## Low-voltage Luminaire

**Model(s):** DDI-240-15-24V-XXXXK-N2, DDI-240-10-12V-XXXXK-N2, DDI-168-5-12V-XXXXK-N2, DDI-240-15-24V-XXXXK-N2-2P, DDI-120-8-24V-XXXXK-A1-N2-DGJIP67, DDI-120-5-12V-XXXXK-N2, DDI-60-8-12V-XXXXK-N2, DDI-240-15-12V-XXXXK-N2-2P, DDI-120-8-12V-XXXXK-A1-N2-DGJIP67, DDI-180-8-12V-XXXXK-N2, DDI-168-8-12V-XXXXK-N2, DDI-120-5-24V-XXXXK-N2, DDI-168-8-24V-XXXXK-N2, DDI-240-10-24V-XXXXK-N2, DDI-240-8-12V-XXXXK-N2, DDI-120-8-24V-XXXXK-N2, DDI-240-10-12V-XXXXK-N2-2P, DDI-120-8-12V-XXXXK-N2, DDI-180-8-24V-XXXXK-N2, DDI-168-5-24V-XXXXK-N2, DDI-240-8-24V-XXXXK-N2, DDI-60-8-24V-XXXXK-N2, DDI-240-15-12V-XXXXK-N2, DDI-240-10-24V-XXXXK-N2-2P *Where "XXXX" can be 2700 thru 6500 to represent the color temperature of LED.*

**Model(s):** DDI-120-8-24V-(XXK+YYK)-N2, DDI-120-8-24V-XXK+YYK-N2-UL-DGJIP67, DDI-120-8-24V-(XXK+YYK)-N2-DGJIP67, DDI-180-8-24V-XXK+YYK-N2, DDI-168-8-24V-(XXK+YYK)-N2, DDI-168-8-12V-(XXK+YYK)-N2, DDI-180-8-12V-XXK+YYK-N2, DDI-120-8-12V-(XXK+YYK)-N2-DGJIP67, DDI-168-5-12V-(XXK+YYK)3X-N2, DDI-120-5-12V-(XXK+YYK)2X-N2, DDI-120-8-24V-XXK+YYK-N2, DDI-168-8-24V-XXK+YYK-N2, DDI-120-5-24V-(XXK+YYK)2X-N2, DDI-120-8-12V-(XXK+YYK)-N2, DDI-192-8-24V-XXK+YYK-N2, DDI-120-5-24V-(XXK+YYK)3X-N2, DDI-192-8-12V-XXK+YYK-N2, DDI-168-8-12V-XXK+YYK-N2, DDI-120-8-12V-(XXK+YYK)2X-N2, DDI-120-5-12V-(XXK+YYK)3X-N2, DDI-168-5-24V-(XXK+YYK)3X-N2, DDI-120-8-12V-XXK+YYK-N2-UL-DGJIP67, DDI-120-8-12V-XXK+YYK-N2, DDI-120-8-24V-(XXK+YYK)2X-N2 *Where "XX" and "YY" can be 2.7 thru 6.5 to represent the color temperature of LED.*



David Piecuch  
UL Mark Certification Program Manager

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

